

Serial No. 09/615,188

Page 2 of 14

IN THE CLAIMS

1. - 15. (canceled)

**RECEIVED
CENTRAL FAX CENTER****APR 25 2007**

16. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in a synchronous transmission frame including data for one or more channels; and

a frame identification section identifying a frame size defined by a scheme of multiplexing one or more of the synchronous transmission frames based on a change in a pointer processing result of said pointer processing section for the data from each of the channel data.

17. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in a synchronous transmission frame; and

a frame identification section for identifying a frame size defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section is composed to perform serially said pointer processing according to a rate based on a transmission rate of said synchronous transmission frame.

18. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in a synchronous transmission frame; and

84210785_1

Serial No. 09/615,188

Page 3 of 14

a frame identification section for identifying a frame size defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said frame identification section is composed to perform serially said identification processing according to a rate based on a transmission rate of said synchronous transmission frame.

19. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a synchronous transmission frame; and

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises:

a pointer detection section for detecting a pointer value contained in a pointer byte of said synchronous transmission frame; and

a concatenation detection section for detecting that said synchronous transmission frame is in concatenation state when respective detection results of said pointer detecting section satisfy a given condition.

20. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a synchronous transmission frame; and

84210785_1

Serial No. 09/615,188

Page 4 of 14

a frame identification section for identifying a frame composition of said synchronous transmission frame based on pointer processing result of said pointer processing section, wherein said pointer processing section comprises:

a pointer detection section for detecting a pointer value contained in a pointer byte of said synchronous transmission frame; and

a concatenation detection section for detecting that said synchronous transmission frame is in concatenation state when respective detection results of said pointer detecting section satisfy a given condition,

wherein said concatenation detection section is composed to detect a state where an NDF-bit indicates an NDF enable, an SS-bit indicates a normal value and said pointer value indicates an NDF enable, an SS-bit indicates a normal value and said pointer value indicates all "1" as said given condition.

21. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a synchronous transmission frame; and

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises a pointer detecting section for detecting at least SS-bit contained in a pointer byte of said synchronous transmission frame; and

said pointer detection section is composed to be able to modify said SS-bit detection condition.

84210785_1

Serial No. 09/615,188

Page 5 of 14

22. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a synchronous transmission frame; and

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section and for providing such identification result to said pointer processing section,

wherein said pointer processing section comprises:

a pointer detection section for detecting an NDF-bit, an SS-bit and a pointer value contained in a pointer byte of said synchronous transmission frame; and

an invalid pointer detection section for detecting that said pointer byte is an invalid byte, based on respective detection results in said pointer section;

in which said invalid pointer detection section is composed to change over a detection condition of a valid pointer byte according to a reception state and a frame composition of said synchronous transmission frame, and to detect as said invalid pointer byte such pointer byte not satisfying said detection condition.

23. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a transmission frame; and

84210785_1

Serial No. 09/615,188

Page 6 of 14

a frame identification section for identifying a frame composition of said transmission frame based on pointer processing result of said pointer processing section and for providing such identification result to said pointer processing section,

wherein said pointer processing section comprises:

a pointer detection section for detecting an NDF-bit, an SS-bit and a pointer value contained in a pointer byte of said transmission frame; and

an invalid pointer detection section for detecting that said pointer byte is an invalid byte, based on respective detection results in said pointer section;

in which said invalid pointer detection section is composed to change over a detection condition of a valid pointer byte according to a reception state and a frame composition of said transmission frame, and to detect as said invalid pointer byte such pointer byte not satisfying said detection condition,

said apparatus further comprising a protection section for outputting an LOP state indication when said invalid pointer byte is detected for given number of times consecutively in said invalid pointer detection.

24. (previously presented) An apparatus comprising:

a pointer processing section for processing a pointer contained in a transmission frame including one or more channel data; and

a frame identification section performing monitoring a change in a pointer processing result of said pointer processing section for each of the channel data to identify a frame size of said transmission frame based on a monitored pointer processing result,

wherein said pointer processing section comprises;

842107M5_1

Serial No. 09/615,188

Page 7 of 14

a pointer detection section for detecting an NDF-bit, an SS-bit and a pointer value contained in a pointer byte of said transmission frame; and

an AIS detection section for detecting an AIS state indication of said pointer byte, based on respective detection results in said pointer detection section;

in which said pointer processing section is composed to be able to output outside an AIS state indication signal as it is, upon the detection of said AIS state indication signal in said AIS detection section.

25. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a transmission frame; and

a frame identification section for identifying a frame composition of said transmission frame based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises;

a pointer detection section for detecting an NDF-bit, an SS-bit and a pointer value contained in a pointer byte of said transmission frame; and

an AIS detection section for detecting an AIS state indication contained in said pointer byte of said transmission frame, based on respective detection results in said pointer detection section;

in which, when said transmission frame includes a leading frame and a dependent frame linked to said leading frame, said pointer processing section is composed to cancel an AIS state of both said leading frame and said dependent frame, upon reception of an NDF enable for said

B4210785_1

Serial No. 09/615,188

Page 8 of 14

pointer byte of said transmission frame, during alarm state processing receiving said AIS state indication of said transmission frame from said alarm detection section.

26. (original) An apparatus according to claim 25:

wherein said pointer processing section is composed to annual said AIS state indication output from said AIS detection section, upon the reception of said NDF enable for said pointer byte of said transmission frame.

27. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in ~~said~~ a synchronous transmission frame; and

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section is composed to perform an alarm state transition processing, upon receiving a higher order group alarm information about said synchronous transmission frame.

28. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in ~~said~~ a synchronous transmission frame; and

84210785_1

Serial No. 09/615,188

Page 9 of 14

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises a pointer value updating section for updating a pointer value contained in a pointer byte of said synchronous transmission frame;

in which said pointer value updating section is composed to perform serially said pointer value updating processing according to a rate based on a transmission rate of said synchronous transmission frame.

29. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in ~~said a~~ synchronous transmission frame; and

a frame identification section for identifying a frame composition defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises a pointer detection section for detecting a pointer byte of said synchronous transmission frame;

in which said frame composition identification section comprises;

an identification condition setting section for setting an identification condition for each frame composition of said synchronous transmission frame; and

a frame composition determination section for determining that said synchronous transmission frame is a frame composition corresponding to said identification condition when

84210785_1

Serial No. 09/615,188

Page 10 of 14

detection results of said pointer detection section satisfy said identification condition in said identification condition setting section.

30. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in said a transmission frame; and

a frame identification section for identifying a frame composition of said transmission frame based on pointer processing result of said pointer processing section,

wherein said pointer processing section comprises a pointer detection section for detecting a pointer byte of said transmission frame;

in which said frame composition identification section comprises;

an identification condition setting section for setting an identification condition for each frame composition of said transmission frame; and

a frame composition determination section for determining that said transmission frame is a frame composition corresponding to said identification condition when detection results of said pointer detection section satisfy said identification condition in said identification condition setting section,

wherein said frame composition determination second is composed to determine that said transmission frame is a frame composition corresponding to a second identification condition when detection results of said pointer detection section has satisfied a first identification condition setting section and then satisfies said second identification, and to cancel said detection results under said first identification condition.

84210785_1

Serial No. 09/615,188

Page 11 of 14

31. **(currently amended)** A reception pointer processing apparatus for receiving a synchronous transmission frame transmitted by a transmission system and for performing pointer processing to said synchronous transmission frame comprising:

a pointer processing section for executing required pointer processing of each unit frame contained in said synchronous transmission frame; and

a frame composition identification section for identifying a concatenation state defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section and for providing such identification result to said pointer processing section.

32. **(currently amended)** A reception pointer processing apparatus for receiving a synchronous transmission frame transmitted by a transmission system and for performing pointer processing to said synchronous transmission frame comprising:

a pointer processing section for executing required pointer processing of each unit frame contained in said synchronous transmission frame; and

a frame composition identification section for identifying a concatenation state defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section and for providing such identification result to said pointer processing section,

wherein said pointer processing section is composed to perform serially said pointer processing according to a rate based on a synchronous transmission frame.

84210785_1

Serial No. 09/615,188

Page 12 of 14

33. (currently amended) A reception pointer processing apparatus for receiving a synchronous transmission frame transmitted by a transmission system and for performing pointer processing to said synchronous transmission frame comprising:

a pointer processing section for executing required pointer processing of each unit frame contained in said synchronous transmission frame; and

a frame composition identification section for identifying a concatenation state defined by a scheme of multiplexing one or more of the synchronous transmission frames based on pointer processing result of said pointer processing section and for providing such identification result to said pointer processing section,

wherein said frame composition identification section is composed to perform serially said identification processing according to a rate based on a transmission rate of said synchronous transmission frame.

34. (currently amended) An apparatus comprising:

a pointer processing section for processing a pointer contained in a synchronous transmission frame including data for one or more channels ~~data~~; and

a frame identification section for identifying a frame size defined by a scheme of multiplexing one or more of the synchronous transmission frames based on monitoring of a pointer processing result of said pointer processing section for the data from each of the channel data and for providing such identification result to said pointer processing section.

84210785_1